

HP Cold Patch RAP 100 Mix

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Revision Date: 04/05/2021 Date of issue: 08/26/2016 Version: 2.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: HP Cold Patch RAP 100 Mix

1.2. Intended Use of the Product

Use of the Substance/Mixture: No use is specified

1.3. Name, Address, and Telephone of the Responsible Party

Company:

Russell Standard
285 Kappa Drive
Suite 300
Pittsburgh, PA 15238

Directory: (800) 323-3053
Main: (412) 449-0700
Fax: (412) 449-0704

www.russellstandard.com

1.4. Emergency Telephone Number

Emergency Number: (800) 255-3924 (24 hours)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US Classification:

| | |
|-----------|------|
| Carc. 1A | H350 |
| STOT SE 3 | H335 |
| STOT RE 1 | H372 |

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US):



GHS07



GHS08

Signal Word (GHS-US): Danger

Hazard Statements (GHS-US):

H335 - May cause respiratory irritation.

H350 - May cause cancer.

H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements (GHS-US):

- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P260 - Do not breathe vapors, mist, or spray.
- P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
- P270 - Do not eat, drink or smoke when using this product.
- P271 - Use only outdoors or in a well-ventilated area.
- P280 - Wear protective gloves, protective clothing, and eye protection.
- P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
- P308+P313 - If exposed or concerned: Get medical advice/attention.
- P312 - Call a poison center or doctor if you feel unwell.
- P314 - Get medical advice/attention if you feel unwell.
- P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
- P405 - Store locked up.
- P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. Hot asphalt can release toxic Hydrogen Sulfide gas. Hydrogen Sulfide can accumulate in vapor space of tanks and vessels during transfer and storage of this material. If stored under heat for extended periods or significantly agitated, this material might evolve or release hydrogen sulfide, a flammable gas, which can raise and widen this material's actual flammability limits and significantly lower its auto-ignition temperature. Hydrogen sulfide is a toxic gas that can be fatal. It also has a rotten egg smell that causes odor fatigue very quickly and shouldn't be used as an indicator for the presence of gas.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product Identifier | % | GHS-US classification |
|---|-------------------------|---------------|---|
| Aggregate (Quartz, slag, limestone, dolomite, etc.) | (CAS No) Not applicable | ≤ 95.5 | Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372 |
| Asphalt | (CAS No) 8052-42-4 | 3.15 - 5.85 | Carc. 2, H351 |
| Proprietary Fuel 1 | (CAS No) Proprietary | 0.4275 - 1.95 | Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 3, H402 Aquatic Chronic 2, H411 |
| Proprietary Fuel 2 | (CAS No) Proprietary | 0.045 - 0.195 | Not classified |

| Name | Product Identifier | % | GHS-US classification |
|-------------------------------------|----------------------|------------------|--|
| Proprietary fatty amine derivative | (CAS No) Proprietary | 0.0225 - 0.13 | Skin Corr. 1B, H314 Eye Dam. 1, H318 |
| Alkanes, C10-20-branched and linear | (CAS No) 928771-01-1 | < 0.0975 | Flam. Liq. 4, H227 Asp. Tox. 1, H304 |
| Proprietary sulfur additive | (CAS No) Proprietary | ≤ 0.00975 | Comb. Dust Skin Irrit. 2, H315 Aquatic Acute 3, H402 |
| Proprietary Fuel 3 | (CAS No) Proprietary | 0.00009 - 0.0039 | Flam. Sol. 2, H228 Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |

Full text of H-phrases: see section 16

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists. Cool skin rapidly with cold water after contact with molten product. Removal of solidified molten material from skin requires medical assistance.

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention. Removal of solidified molten material from the eyes requires medical assistance.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: May cause respiratory irritation. May cause cancer. Causes damage to organs through prolonged or repeated exposure. Risk of thermal burns on contact with molten product.

Symptoms/Injuries After Inhalation: Irritation of the respiratory tract and the other mucous membranes. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a seriously disabling and fatal lung disease. **WARNING:** irritating and toxic hydrogen sulfide gas may be present. Greater than 15-20 ppm continuous exposure can cause mucous membrane and respiratory tract irritation. 50-500 ppm can cause headache, nausea, and dizziness. Continued exposure at these levels can lead to loss of reasoning and balance, difficulty in breathing, fluid in the lungs, and possible loss of consciousness. Greater than 500 ppm can cause rapid unconsciousness and death if not promptly revived.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation. Risk of thermal burns on contact with molten product.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: May cause cancer. Causes damage to organs through prolonged or repeated exposure. Emissions from asphalt are suspected of causing cancer. If dust is generated, repeated exposure through inhalation may cause cancer or lung disease. Repeated or prolonged exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss. Long term exposure

to respirable crystalline silica results in a significant risk of developing silicosis and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Earth. Sand. Dry chemical, alcohol-resistant foam, carbon dioxide.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire. Do not use water when molten material is involved, contact of hot product with water will result in a violent expansion as the water turns to steam causing explosion with massive force.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive. Contains a small amount of hydrogen sulfide. Heating of this product and storage under elevated temperatures or over long periods of time may release higher amounts of flammable hydrogen sulfide.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Nitrogen oxides. Hydrocarbons. Sulfur oxides. Hydrogen sulfide. Silicon oxides.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe vapor, mist or spray. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. If melted: allow liquid to solidify before taking it up. If spilled directly onto the ground, remove sufficient soil to ensure material is fully recovered.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with eyes, skin and clothing. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/mist/vapors/spray.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Products: Strong acids, strong bases, strong oxidizers. Chlorates. Hydrofluoric acid. Reducing agents. When molten: water.

7.3. Specific End Use(s)

No use is specified.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

| Asphalt (8052-42-4) | | |
|---------------------|--|--|
| USA ACGIH | ACGIH TWA (mg/m ³) | 0.5 mg/m ³ (fume, inhalable fraction) |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen fume, coal tar-free |
| USA ACGIH | Biological Exposure Indices (BEI) | (Medium: urine - Time: end of shift at end of workweek - Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)) |
| USA NIOSH | NIOSH REL (ceiling) (mg/m ³) | 5 mg/m ³ (fume) |

| Proprietary Fuel 1 (Proprietary) | | |
|----------------------------------|--------------------------------|--|
| USA ACGIH | ACGIH TWA (mg/m ³) | 100 mg/m ³ (inhalable fraction and vapor) |
| USA ACGIH | ACGIH chemical category | Skin - potential significant contribution to overall exposure by the cutaneous route, Confirmed Animal Carcinogen with Unknown Relevance to Humans |

| Proprietary Fuel 3 (Proprietary) | | |
|----------------------------------|-------------------------|--|
| USA ACGIH | ACGIH TWA (ppm) | 10 ppm |
| USA ACGIH | ACGIH chemical category | Skin - potential significant contribution to overall exposure by the cutaneous route, Confirmed Animal Carcinogen with Unknown Relevance to Humans |

HP Cold Patch RAP 100 Mix

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

| | | |
|-----------|---------------------------------------|---|
| USA ACGIH | Biological Exposure Indices (BEI) | (Time: end of shift - Parameter: 1-Naphthol with hydrolysis plus 2-Naphthol with hydrolysis (nonquantitative, nonspecific)) |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 50 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (ppm) | 10 ppm |
| USA NIOSH | NIOSH REL (STEL) (mg/m ³) | 75 mg/m ³ |
| USA NIOSH | NIOSH REL (STEL) (ppm) | 15 ppm |
| USA IDLH | US IDLH (ppm) | 250 ppm |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 50 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 10 ppm |

| Limestone (1317-65-3) | | |
|-----------------------|--------------------------------------|--|
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust) |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) |

| Quartz (14808-60-7) | | |
|---------------------|--------------------------------------|---|
| USA ACGIH | ACGIH TWA (mg/m ³) | 0.025 mg/m ³ (respirable particulate matter) |
| USA ACGIH | ACGIH chemical category | A2 - Suspected Human Carcinogen |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 0.05 mg/m ³ (respirable dust) |
| USA IDLH | US IDLH (mg/m ³) | 50 mg/m ³ (respirable dust) |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 50 µg/m ³ |

8.2. Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Thermal Hazard Protection: When working with hot material, use suitable thermally protective clothing.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State: Solid

Appearance: No data available

Odor: No data available

Odor Threshold: No data available

pH: No data available

Evaporation Rate: No data available

Melting Point: No data available

Freezing Point: No data available

Boiling Point: No data available

Flash Point: No data available

Auto-ignition Temperature: No data available

Decomposition Temperature: No data available

Flammability (solid, gas): No data available

Vapor Pressure: No data available

Relative Vapor Density at 20°C: No data available

Relative Density: No data available

Solubility: No data available

Partition Coefficient: N-Octanol/Water: No data available

Viscosity: No data available

9.2. Other Information

No additional information available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Hazardous reactions will not occur under normal conditions.

10.2. Chemical Stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

10.4. Conditions to Avoid

Direct sunlight, extremely high or low temperatures, and incompatible materials.

10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers. Chlorates. Hydrofluoric acid. Reducing agents. When molten: water.

10.6. Hazardous Decomposition Products

None known.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity: Not classified

HP Cold Patch RAP 100 Mix

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

| Asphalt (8052-42-4) | |
|---------------------|--------------------------|
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rabbit | > 2000 mg/kg |
| LC50 Inhalation Rat | > 94.4 mg/m ³ |

| Proprietary Fuel 1 (Proprietary) | |
|----------------------------------|-------------------|
| LD50 Oral Rat | 18.7 - 24.9 ml/kg |
| LD50 Dermal Rabbit | > 4300 mg/kg |
| LC50 Inhalation Rat | 3.6 mg/l/4h |

| Proprietary sulfur additive (Proprietary) | |
|---|----------------|
| LD50 Oral Rat | > 3000 mg/kg |
| LD50 Dermal Rabbit | > 2000 mg/kg |
| LC50 Inhalation Rat | > 9.23 mg/l/4h |

| Proprietary Fuel 3 (Proprietary) | |
|----------------------------------|--|
| LD50 Oral Rat | 533 - 710 mg/kg |
| LC50 Inhalation Rat | > 340 mg/m ³ (Exposure time: 1 h) |
| ATE (Oral) | 533.00 mg/kg body weight |

| Slags, ferrous metal, blast furnace (65996-69-2) | |
|--|---|
| LD50 Oral Rat | > 2000 mg/kg |
| LD50 Dermal Rat | > 4000 mg/kg |
| LC50 Inhalation Rat | > 230.1 mg/m ³ (Exposure Time: 6 h; Species: Wistar) |

| Quartz (14808-60-7) | |
|---------------------|--------------|
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rat | > 5000 mg/kg |

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer.

| Asphalt (8052-42-4) | |
|---|---|
| IARC group | 2B |
| National Toxicology Program (NTP) Status | Twelfth Report - Items under consideration. |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |

| Proprietary Fuel 3 (Proprietary) | |
|---|--|
| IARC group | 2B |
| National Toxicology Program (NTP) Status | Reasonably anticipated to be Human Carcinogen. |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |

HP Cold Patch RAP 100 Mix

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

| Quartz (14808-60-7) | |
|---|---|
| IARC group | 1 |
| National Toxicology Program (NTP) Status | Known Human Carcinogens. |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs through prolonged or repeated exposure.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Irritation of the respiratory tract and the other mucous membranes. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a seriously disabling and fatal lung disease. **WARNING:** irritating and toxic hydrogen sulfide gas may be present. Greater than 15-20 ppm continuous exposure can cause mucous membrane and respiratory tract irritation. 50-500 ppm can cause headache, nausea, and dizziness. Continued exposure at these levels can lead to loss of reasoning and balance, difficulty in breathing, fluid in the lungs, and possible loss of consciousness. Greater than 500 ppm can cause rapid unconsciousness and death if not promptly revived.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation. Risk of thermal burns on contact with molten product.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: May cause cancer. Causes damage to organs through prolonged or repeated exposure. Emissions from asphalt are suspected of causing cancer. If dust is generated, repeated exposure through inhalation may cause cancer or lung disease. Repeated or prolonged exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss. Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Not classified.

| Proprietary Fuel 1 (Proprietary) | |
|----------------------------------|---|
| LC50 Fish 1 | 57 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |

| Proprietary sulfur additive (Proprietary) | |
|---|---|
| LC50 Fish 1 | 866 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static]) |
| EC50 Daphnia 1 | 736 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LC50 Fish 2 | 14 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |

| Proprietary Fuel 3 (Proprietary) | |
|----------------------------------|--|
| LC50 Fish 1 | 5.74 - 6.44 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1 | 2.16 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LC50 Fish 2 | 1.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through]) |
| EC50 Daphnia 2 | 1.96 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through]) |

12.2. Persistence and Degradability

| | |
|-------------------------------|------------------|
| HP Cold Patch RAP 100 Mix | |
| Persistence and Degradability | Not established. |

12.3. Bioaccumulative Potential

| | |
|---------------------------|------------------|
| HP Cold Patch RAP 100 Mix | |
| Bioaccumulative Potential | Not established. |

| | |
|---------------------|-------------------------------|
| Asphalt (8052-42-4) | |
| BCF Fish 1 | (no bioaccumulation expected) |
| Log Pow | > 6 |

| | |
|----------------------------------|----------------|
| Proprietary Fuel 3 (Proprietary) | |
| BCF Fish 1 | 30 - 430 |
| Log Pow | 3.3 (at 20 °C) |

| | |
|--|----------------------------|
| Dolomite (CaMg(CO ₃) ₂) (16389-88-1) | |
| BCF Fish 1 | (no known bioaccumulation) |

12.4. Mobility in Soil

No additional information available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Not regulated for transport

14.2. In Accordance with IMDG

Not regulated for transport

14.3. In Accordance with IATA

Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

| | |
|--|---------------------------------|
| HP Cold Patch RAP 100 Mix | |
| SARA Section 311/312 Hazard Classes | Health hazard – Carcinogenicity |
| Health hazard - Specific target organ toxicity (single or repeated exposure) | |

| | |
|---|--|
| Asphalt (8052-42-4) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

| | |
|---|--|
| Proprietary Fuel 1 (Proprietary) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

| | |
|---|--|
| Alkanes, C10-20-branched and linear (928771-01-1) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

| | |
|---|--|
| Proprietary sulfur additive (Proprietary) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

| | |
|--|---|
| Proprietary Fuel 3 (Proprietary) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 | |
| EPA TSCA Regulatory Flag | T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA |
| CERCLA RQ | 100 lb |
| SARA Section 313 - Emission Reporting | 0.1 % |

| | |
|---|--|
| Slags, ferrous metal, blast furnace (65996-69-2) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

| | |
|---|--|
| Limestone (1317-65-3) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

| | |
|---|--|
| Dolomite (CaMg(CO ₃) ₂) (16389-88-1) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

| | |
|---|--|
| Quartz (14808-60-7) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

15.2. US State Regulations

| | |
|---|--|
| Proprietary Fuel 3 (Proprietary) | |
| U.S. - California - Proposition 65 - Carcinogens List | WARNING: This product contains chemicals known to the State of California to cause cancer. |

| | |
|---|--|
| Quartz (14808-60-7) | |
| U.S. - California - Proposition 65 - Carcinogens List | WARNING: This product contains chemicals known to the State of California to cause cancer. |

HP Cold Patch RAP 100 Mix

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Asphalt (8052-42-4)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Proprietary sulfur additive (Proprietary)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Proprietary Fuel 3 (Proprietary)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

Limestone (1317-65-3)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Quartz (14808-60-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date: 07/05/2018

Other Information: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

| GHS Full Text Phrases | |
|--|---|
| Acute Tox. 4 (Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 4 |
| Acute Tox. 4 (Oral) | Acute toxicity (oral) Category 4 |
| Aquatic Acute 1 | Hazardous to the aquatic environment - Acute Hazard Category 1 |
| Aquatic Acute 3 | Hazardous to the aquatic environment - Acute Hazard Category 3 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment - Chronic Hazard Category 1 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment - Chronic Hazard Category 2 |
| Asp. Tox. 1 | Aspiration hazard Category 1 |
| Carc. 1A | Carcinogenicity Category 1A |
| Carc. 2 | Carcinogenicity Category 2 |
| Comb. Dust | Combustible Dust May form combustible dust concentrations in air |
| Eye Dam. 1 | Serious eye damage/eye irritation Category 1 |
| Flam. Liq. 3 | Flammable liquids Category 3 |
| Flam. Liq. 4 | Flammable liquids Category 4 |
| Flam. Sol. 2 | Flammable solids Category 2 |
| Skin Corr. 1B | Skin corrosion/irritation Category 1B |

HP Cold Patch RAP 100 Mix

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

| GHS Full Text Phrases | |
|-----------------------|---|
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| STOT RE 1 | Specific target organ toxicity (repeated exposure) Category 1 |
| STOT RE 2 | Specific target organ toxicity (repeated exposure) Category 2 |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| H226 | Flammable liquid and vapor |
| H227 | Combustible liquid |
| H228 | Flammable solid |
| H302 | Harmful if swallowed |
| H304 | May be fatal if swallowed and enters airways |
| H314 | Causes severe skin burns and eye damage |
| H315 | Causes skin irritation |
| H318 | Causes serious eye damage |
| H332 | Harmful if inhaled |
| H335 | May cause respiratory irritation |
| H350 | May cause cancer |
| H351 | Suspected of causing cancer |
| H372 | Causes damage to organs through prolonged or repeated exposure |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| H400 | Very toxic to aquatic life |
| H402 | Harmful to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |
| H411 | Toxic to aquatic life with long lasting effects |

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)